


Replace your aging Prompter with a Tekskil High Performance LCD

Tekskil's 15 inch LCD Prompter Monitors are the ultimate in rugged performance, guaranteed to perform under the most challenging conditions. Custom electronics and optics combine for enhanced readability – the highest rated standard prompting systems available. From the entry level **Value Series** which offers Tekskil's legendary quality display at an economical price, to the new **Premium Series** for the ultimate in performance and brightness. They incorporate enhanced LCD panels (improved brightness and contrast), special optics, and surrounded with metal enclosures.

- Tekskil prompters are serious professional grade products and feature ultra-lightweight folded metal enclosures for maximum strength.
- Come complete with the latest LED backlight technology, high resolution displays having up to 1000 cd/m² (nits) of brightness and a 2000:1 contrast ratio which is necessary for those difficult outdoor shots
- Push button selection of SelectVIEW screen size to allow the talent to read the text at any distance without looking "shifty eyed" or squinting
- Can be configured with a front mounted LED Tally light
- Optional Anton-Bauer Compact Battery Bracket supports industry standard batteries and provides up to four hours of continuous use.

As you can see, the beamsplitter support and prompter panel mount is located approximately one third back from the front of the rail. The Ultralight Prompter panel sits on top of the rail and attaches to the beamsplitter support. With the sliding captive nuts in the full length channel on the underside of the rail, the center of gravity can be moved forward of the beamsplitter and able to static balance perfectly with no counterweights. The camera becomes the counterweight. More adjustment is available with the sliding camera riser, shown here with our R47 Ultra High Riser for mini DV and small box cameras. Tekskil manufactures a complete line of camera risers to accommodate the largest EFP camera or the smallest mini-DV camcorder.

	15V	15P
	High Bright Active Matrix TFT LCD	
Production Usage:	Indoor Only	Indoor/Outdoor
Diagonal Screen Size	15.0 inches	15.0 inches
(HxV):	(11.7" x 9")	(11.7" x 9")
Pixel Format (RGB):	1024 x 768	1280 x 1024
LED Backlight:	400+ cd/m ²	1000 cd/m ²
Contrast Ratio:	2000:1	2000:1
Viewing Angle (H/V):	170º / 170º	170º / 170º
Weight of display:	9.5 lbs.	9 lbs.
Lamp Life:	30,000-Hour	60,000-Hour
Power Consumption:	36 W	28 W
Warranty:	One Year	Five Years





Set up one of our systems in your studio and see the difference for yourself

A Tekskil Field Teleprompter is a proven solution

Contact us for details.

Tekskil Industries, Inc.