Tekskil's 22P HD-SDI / Analog prompter is the solution for Studios requiring switched dual input video capability to their prompter display.

This impressive 22 inch monitor is the largest camera mounted prompter available.

The 22P-HD/SDI combines the latest in enhanced LCD displays with supercharged brightness and sophisticated optics (screen bonded glass micro-laminates) to deliver the best readability of any prompter. The energy-efficient LED backlights are bright, light and tough, the custom electronics ensure image quality with non-stop management of signal, power and temperature, and the all-metal housing is an engineered fusion of strength, rigidity, and light weight.

This prompting system can be complemented with a 22 inch HD Aux /Talent Assist display; this configuration is an excellent match for the latest generation of mid-weight robotic pan & tilt pedestals. The innovative modular design enables the 22P-HD/SDI to quickly be reconfigured for field or Outdoor Broadcasting or even as a Presidential Speech Prompter. Re-staging is simplified with Tekskil's proprietary quick release mounting system and a comprehensive choice of conversion kits.

- Switchable Composite/SDI/HD-SDI is standard 3G:SMPTE 424M@2.97 and 2.967Gb/s 1080p@60/59.94/50Hz HD:SMPTE 292M/274M/296M@1.485 and 1.435Gb/s 1080i@60/59.94/50Hz 1080p/psf@30/29.97/25/24/23.98Hz 720p@60/59.94/50/30/29.97/25/24/23.98Hz SD:SMPTE 259M@270Mb/s 625i50 525i59.94
- 22P-HD/SDI system will support a 22" HD auxiliary display dynamically suspended underneath the prompter and dampened to be free of vibration
- Available with a front-mounted single stage tally light or a topmounted dual stage TallyCAM display
- Affordably priced

22P Specifications

High Bright Active Matrix TFT LCDDiagonal Screen Size (HxV):22 inches (18Pixel Format (RGB):1680 xBacklight:LED 100Contrast Ratio:200Viewing Angle (H/V):160° /Switchable Video Inputs:CompositeWeight of display only:16 lWeight of System w/o Aux:56 lLamp Life:60,000Power Consumption:34 WWarranty:Five Y

22 inches (18.65" x 11.65") 1680 x 1050 LED 1000 cd/m² 2000:1 160° / 160° Composite to HD-SDI 16 lbs. 56 lbs. 60,000-Hour 34 Watts Five Years



22P with Wide Angle Studio Hood, 22 inch Aux Panel and TallyCAM

A Tekskil LCD Teleprompter is a proven solution – contact us for details

Set up one of our systems in your studio and see the difference for yourself

Tekskil Industries, Inc. Toll Free 877-TEKSKIL (835-7545)

Toll Free Fax: 877-576-8361 Email: <u>Team@tekskil.com</u>