

Tekskil Universal 19" Replacement LCD

Replace your aging LCD Prompter with a Tekskil High Performance LED Replacement Prompter

Failing LCD prompter displays are a frequent headache for broadcasters – these critical talent support products lose contrast, go dim, or shut down altogether without warning.

Tekskil's 19RE prompter display is our solution for the multitude of stations fed up with the downtime and cost of unreliable prompter monitors. The 19RE is a purpose built replacement monitor engineered to end the headaches of failing displays with benchmark reliability, features, installation ease and cost.



<u>Reliability</u>: The 19RE monitor incorporates a high bright LED backlit display with twin cooling fans and DC power management, all housed in a rugged welded aluminum enclosure.

<u>Features</u>: The 19RE provides three image sizes – 15", 17" and 19" – user selectable from the built-in custom scaler. Enhanced contrast and panel brightness provide a crisp, easy to read talent display. Power consumption is minimized with long-life energy efficient LED edge lights. The Tekskil universal replacement monitor can be configured to replace your existing heads by simply switching the display size electronically - making it possible to optimize display size to the beamsplitter format and to actively reconfigure for tight versus distant shots.

<u>Installation</u>: The 19RE has the correct mounting hardware built in for simple replacement of those failing displays sold by other prompter companies. No additional brackets or adapters required. You reuse your existing tally system, nothing could be simpler!

<u>Cost</u>: The 19RE monitor is half the cost (or less) of similar displays, and comes with an unheard of 7 year warranty. We've built it to last and we're prepared to stand behind it.

19RE specifications

Diagonal Screen Size: 19 inches

(H x V) (14.8" x 11.9")

Pixel Format (RGB): 1280 x 1024 (Native)

LED Backlight Brightness: 700 cd/m² (approx 700 Nits)

Contrast Ratio: 2000:1

Viewing Angle (H/V): 150° / 150° minimum

Composite Video (CVBS) Input: BNC (x1)
Display Weight (complete): 8.0 lbs.

Lamp Life: 80,000+ hours

12 VDC Input: Industry Standard XLR 4-Pin Male (x1)

Power Consumption: 44 Watts (12 VDC)
Warranty: Seven years

Tired of getting the runaround from your current supplier?
Contact Tekskil for a quality, cost effective display solution...

Tekskil Industries, Inc.

Phone: 604 985-2250 Toll Free: 877-TEKSKIL (835-7545) Toll Free Fax: 877 576-8361 Website: Tekskil.com Email: Team@tekskil.com