



<h2>Prompter Selection Guide</h2> <p>877-TEKSKIL Tekskil.com</p>	CPT-70D Load: 8.8 lbs.	EPT-5E-10D Load: 22 lbs.		
				
Specifications	10R Prompter	15R DBC Prompter	15RP DBC Prompter	
Brightness (cd/m ²)	1200	600	1600	
Contrast Ratio	1000	600	1000	
Power Consumption (12 VDC)	18 Watts	32 Watts	24 Watts	
Panel Weight	4.5 lbs.	7 lbs.	7 lbs.	
Warranty	5 Years	1 Year	5 Years	
Dynamically Balanced Cradle	✓	✓	✓	
Prompter Options	Beamsplitters			
	Standard 16:9 HD lens	✓	✓	✓
	Wide Angle 16:9 HD lens	✓	✓	✓
	Tally Option			
	Front mount single-stage LED cluster	✓	✓	✓
	Top mount dual-stage LED bars & Cam #	--	✓	✓
	Timing Option			
6 digit VITC SMPTE clock, 2.3" high LEDs	--	✓	✓	

Tekskil Displays feature: Sophisticated power management to prevent image distortion, electrical noise and display damage
 Signal conditioning to eliminate ground loops and drop-outs
 Temperature control elements, including twin cooling fans to prevent image loss, back light failure and circuitry overheats

Tekskil Prompting Systems feature: Integrated stabilization and dampening elements to minimize vibration and lurching during camera movement
 Micro-truss construction provides optimal strength, balance and weight for **greatly** reduced pan/tilt servo stress and failure